

Datum: 14.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-el.mag.vent.,NC,vod. krm., 24V DC,5W,NBR,G1/2,0.2-16bar

Kategorija: [Solenoid valve, NC, pilot-operated](#)
Šifra: **102940RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24V DC, 5W, Medium temp. -10°C to 90°C, NBR, G 1/2, PN 0.2 - 16bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/2
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.2
Vrsta	5
DN	13
Max. obratovalni tlak [bar]	16
A [mm]	40.0
Max. sobna temperatura [°C]	60
B [mm]	66.0
Max. temperatura medija [°C]	90