

Datum: 14.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-el.mag.vent.,NC,vod. krm.,24V DC,8W,NBR,G2,0.2-10bar

Kategorija: [Solenoid valve, NC, pilot-operated](#)
Šifra: **102946RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24V DC, 8W, Medium temp. -10°C to 90°C, NBR, G 2, PN 0.2 - 10bar
Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 2
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.2
Vrsta	6
Max. obratovalni tlak [bar]	10
DN	50
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	90
B [mm]	172.0