



**2/2-el.mag.vent.,NO,vod. krm.,  
230-240V,NBR,G1/2,0.2-16bar**

Kategorija: [Solenoid valve, NO, pilot-operated](#)  
Šifra: **102948RIE**

(slika je simbolična)

## Kratek opis

2/2-way solenoid valve brass, NO, pilot operated, 230-240V, 50-60Hz, 16VA, Medium temp. -10°C to 90°C, NBR, G 1/2, PN 0.2 - 16bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Tehnične Specifikacije

|                              |                                      |
|------------------------------|--------------------------------------|
| Min. sobna temperatura [°C]  | -10                                  |
| Min. temperatura medija [°C] | -10                                  |
|                              | For connector socket                 |
| Električni priključek        | Pg 9/Pg 11 acc. to ISO 4400          |
| Ffunkcija                    | normally open (NO)                   |
| IP zaščita                   | IP 65 (with connector socket fitted) |
| Navoj                        | G 1/2                                |
| Notranji deli                | Stainless steel                      |
| Ohišje                       | Brass                                |
| Sedež ventila                | Brass                                |
| Tesnilo                      | NBR                                  |
| Min. obratovalni tlak [bar]  | 0.2                                  |
| Vrsta                        | 4                                    |
| DN                           | 13                                   |
| Max. obratovalni tlak [bar]  | 16                                   |
| A [mm]                       | 54.0                                 |
| B [mm]                       | 66.0                                 |
| Max. sobna temperatura [°C]  | 80                                   |
| Max. temperatura medija [°C] | 90                                   |