



## 2/2-el.mag.vent.,NO,vod. krm.,24V DC,NBR,G3/4,PN0.2-16bar

Kategorija: [Solenoid valve, NO, pilot-operated](#)  
Šifra: **102956RIE**

(slika je simbolična)

### Kratek opis

2/2-way solenoid valve brass, NO, pilot operated, 24 V DC,  
Medium temperature -10 °C to 90 °C, G 3/4, PN 0.2 - 16 bar  
Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or  
low-viscosity, neutral media.

### Tehnične Specifikacije

|                              |                                                        |
|------------------------------|--------------------------------------------------------|
| Min. sobna temperatura [°C]  | -10                                                    |
| Min. temperatura medija [°C] | -10                                                    |
| Električni priključek        | For connector socket<br>Pg 9/Pg 11 acc. to<br>ISO 4400 |
| Ffunkcija                    | normally open (NO)                                     |
| IP zaščita                   | IP 65 (with connector<br>socket fitted)                |
| Navoj                        | G 3/4                                                  |
| Notranji deli                | Stainless steel                                        |
| Ohišje                       | Brass                                                  |
| Sedež ventila                | Brass                                                  |
| Tesnilo                      | NBR                                                    |
| Min. obratovalni tlak [bar]  | 0.2                                                    |
| Vrsta                        | 6                                                      |
| Max. obratovalni tlak [bar]  | 16                                                     |
| DN                           | 19                                                     |
| A [mm]                       | 54.0                                                   |
| Max. sobna temperatura [°C]  | 80                                                     |
| Max. temperatura medija [°C] | 90                                                     |
| B [mm]                       | 104.0                                                  |