

Datum: 11.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-potni el.mag. ventil, NC, direk. upr., 230 V, 50 - 60 Hz

Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102820RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve, brass, NC, direc. operat., 230V, 50-60Hz, Med. temp. -15 to 100°C, Ambient temp. -15 to 55°C, FPM, G 1/8, PN 0-12bar
Standard series, proven over many years, available in three different versions
- Directly operated
- Combined operation
- Pilot-operated
For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Električni priključek	ISO 4400, cable socket (Pg 11P)
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	G 1/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	FPM
Vrsta	1
DN	3.2
Max. obratovalni tlak [bar]	12
B [mm]	30.0
Max. sobna temperatura [°C]	55
A [mm]	75.0
Max. temperatura medija [°C]	100