



2/2-potni el.mag. ventil NC, vod. krm., 24 V DC, G 1

Kategorija: [Solenoid valve, NC, pilot-operated, 24 V DC](#)
Šifra: **116561RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve, Brass, NC, pilot operated, 24 V DC, Medium temperature max. 80 °C / 90 °C, G 1, PN 0.5 - 10 bar

Standard series available in two different versions:

- Directly operated
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4.

Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4.

Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Tehnične Specifikacije

IP zaščita	IP 65
Navoj	G 1
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	FPM
Min. obratovalni tlak [bar]	0.5
Vrsta	3
Max. obratovalni tlak [bar]	10
DN	25
A [mm]	70.0
B [mm]	92.0
C [mm]	124.0