

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## 2/2-potni el.mag. ventil, NC, vod. krm., 24 V DC, 3/4

Kategorija: [Solenoid valve, NC, pilot-operated](#)  
Šifra: **102871RIE**

### Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24 V DC,  
Medium temperature -20 °C to 85 °C, Rp 3/4, PN 0.35 - 7 bar  
Standard series, proven over many years, available in three  
different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or  
low-viscosity, neutral media.

### Tehnične Specifikacije

|                              |                                        |
|------------------------------|----------------------------------------|
| Min. sobna temperatura [°C]  | -20                                    |
| Min. temperatura medija [°C] | -20                                    |
| Električni priključek        | ISO 4400; cable<br>socket (Pg 11P)     |
| Ffunkcija                    | normally closed (NC)                   |
| IP zaščita                   | IP65 (with connector<br>socket fitted) |
| Navoj                        | Rp 3/4                                 |
| Notranji deli                | Stainless steel                        |
| Ohišje                       | Brass                                  |
| Sedež ventila                | Brass                                  |
| Standardni navoj             | Rp thread acc. to ISO<br>7-1           |
| Tesnilo                      | NBR                                    |
| Min. obratovalni tlak [bar]  | 0.35                                   |
| Vrsta                        | 3                                      |
| Max. obratovalni tlak [bar]  | 7                                      |
| DN                           | 19                                     |
| Max. sobna temperatura [°C]  | 50                                     |
| B [mm]                       | 71.0                                   |
| A [mm]                       | 80.0                                   |
| Max. temperatura medija [°C] | 85                                     |