

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-potni el.mag.vent.AISI 304,FPM,NC,direkt.krm.24V,NPT1/8

Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102974RIE**

(slika je simbolična)

Kratek opis

2/2-way sol. valve,AISI 304,FPM,NC,directly op.,24 V
DC,med. temp. -15 °C - 120 °C,amb.temp.-15°C - 55°C,NPT
1/8, PN 0-14 bar
Available versions
- Directly operated
- Combined operation

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Električni priključek	For Pg 11P connector socket acc. to DIN 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	NPT 1/8
Notranji deli	Stainless steel
Ohišje	Stainless steel 1.4301
Sedež ventila	Stainless steel 1.4301
Tesnilo	FPM
Vrsta	1
DN	2.4
Max. obratovalni tlak [bar]	14
B [mm]	30.0
Max. sobna temperatura [°C]	55
A [mm]	91.0
Max. temperatura medija [°C]	120