

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

2/2-potni el.mag.ventil,AISI 304,NBR,NC,direkt.krm.,24 V ,G 1/4

Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102975RIE**

Kratek opis

2/2-way sol. valve,AISI 304,NBR,NC,directly op.,24 V
DC,med. temp. -25 °C - 80 °C,amb.temp.-25°C - 55°C,G 1/4,
PN 0-3.5 bar
Available versions
- Directly operated
- Combined operation

Tehnične Specifikacije

Min. sobna temperatura [°C]	-25
Min. temperatura medija [°C]	-25
Električni priključek	For Pg 11P connector socket acc. to DIN 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	G 1/4
Notranji deli	Stainless steel
Ohišje	Stainless steel 1.4301
Sedež ventila	Stainless steel 1.4301
Tesnilo	NBR
Vrsta	2
Max. obratovalni tlak [bar]	3.5
DN	4
B [mm]	40.0
Max. sobna temperatura [°C]	55
Max. temperatura medija [°C]	80
A [mm]	95.0