

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## 3-pot. krog. ventil, Stinard, L-izpust, nikljana med., 1/2

Kategorija: [3-way ball valves standard type with L-bore](#)  
Šifra: **103377RIE**

### Kratek opis

3-way ball valve, Standard, L-hole, nickel-plated brass,  
Medium / ambient temp. -10 °C to 120 °C, Rp 1/2, DN 15, PN  
max. 40 bar  
3-way ball valves with full bore for diverting media.  
Applications: Water, non-toxic gases, plumbing and heating  
systems, oils, general industrial applications, diesel fuel

### Tehnične Specifikacije

|                                 |                                    |
|---------------------------------|------------------------------------|
| Min. sobna temperatura<br>[°C]  | -10                                |
| Min. temperatura medija<br>[°C] | -10                                |
| Material navojev                | Brass with a bare metal<br>surface |
| Navoj                           | Rp 1/2                             |
| Notranji deli                   | Nickel-plated brass                |
| Ohišje                          | Nickel-plated brass                |
| Ročica                          | Aluminium, painted<br>black        |
| Standardni navoj                | Rp thread acc. to ISO<br>7-1       |
| Tesnilo                         | PTFE                               |
| DN                              | 15                                 |
| PN [bar]                        | 40                                 |
| B [mm]                          | 64.0                               |
| L [mm]                          | 69.0                               |
| A [mm]                          | 100.0                              |
| Max. sobna temperatura<br>[°C]  | 120                                |
| Max. temperatura medija<br>[°C] | 120                                |