

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

3-way ball valve, T-hole, Stainless steel 1.4408, G 2, DN 50

Kategorija: [553](#)
Šifra: **135935RIE**

Kratek opis

3-way ball valve, T-hole, Stainless steel 1.4408, G 2, DN 50,
Operating temperature -20 °C to 180 °C, PN max. 63 bar
With L or T-bore, reduced bore.
Version for sealing on all sides with integrated ISO flange
plate (ISO 5211).
The lever can be turned 360° to allow several switching
variants.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock ISO 5211	ca. 7.9 F 07
Krogelno tesnilo	RTFE (15 % glass fibre reinforced PTFE)
Krogla	Stainless steel 1.4401
Navoj	G 2
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	RTFE (15 % glass fibre reinforced PTFE)
H2 [mm]	14.0
C Ø [mm]	38.1
DN	50
Delovni tlak	63 bar (dependent on temperature)
H1 [mm]	87.4
B [mm]	129.9
L [mm]	149.0
Max. delovna temperatura [°C]	180
A [mm]	197.5