

Datum: 13.05.2024



(slika je simbolična)

3/2 Vklopni ventil »G«, 230 V AC / 50 Hz, Velikost 400, G 3/8

Kategorija: [Start-up valve, power supply 230 V AC, 50 Hz](#)Šifra: **116350RIE**

Kratek opis

3/2-way start-up valve »G«, 230 V AC / 50 Hz, with mounting bracket and silencer, Size 400, G 3/8, Input pressure 2.5 - 9 bar

Combined shut-off and pressure build-up valve (start-up valve). Operated by secondary pressure for controlled pressurisation of pneumatic systems.

The 3/2-way valve opens when the solenoid is activated.

The full cross-section of the valve is open when the working pressure is 50% of the input pressure. When the solenoid is deactivated, the 3/2-way valve closes and the pressure in the line is exhausted via the regulator. With adjustable restrictor.

Tehnične Specifikacije

Električni priključek

Device plug PG 9,
type B

Merjenje pretoka

At $P_1 = 8$ bar, $P_2 = 6$
bar and pressure drop
 $\Delta p = 1$ bar

Navoj

G 3/8

Ohišje

Die-cast aluminium

Serija

G

Tesnilo

NBR

Min. vhodni tlak [bar]

2.5

Max. vhodni tlak [bar]

9

D [mm]

40.5

Max. sobna temperatura
[°C]

70

Max. temperatura medija
[°C]

70

A [mm]

78.0

C [mm]

102.0

B [mm]

142.5

Velikost

400

Pretok [l/min]

4500