

Datum: 14.05.2024



(slika je simbolična)

3/2 Vklopni ventil »G-mali«, 230 V AC/50 Hz, Velikost 200, G 1/4

Kategorija: [Start-up valve, power supply 230 V AC, 50 Hz](#)Šifra: **116342RIE**

Kratek opis

3/2-way start-up valve »G-mini«, 230 V AC / 50 Hz, with mounting bracket and silencer, Size 200, G 1/4, Input pressure 2.5 - 9 bar

Combined shut-off and pressure build-up valve (start-up valve). Operated by secondary pressure for controlled pressurisation of pneumatic systems.

The 3/2-way valve opens when the solenoid is activated.

The full cross-section of the valve is open when the working pressure is 50% of the input pressure. When the solenoid is deactivated, the 3/2-way valve closes and the pressure in the line is exhausted via the regulator. With adjustable restrictor.

Tehnične Specifikacije

Električni priključek

Device plug PG 9, type B

Merjenje pretoka

At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar

Navoj

G 1/4

Ohišje

Die-cast aluminium

Serija

GA-mini

Tesnilo

NBR

Min. vhodni tlak [bar]

2.5

Max. vhodni tlak [bar]

9

D [mm]

30.0

A [mm]

59.0

Max. sobna temperatura [°C]

70

Max. temperatura medija [°C]

70

C [mm]

93.5

B [mm]

123.5

Velikost

200

Pretok [l/min]

550