

## Active charcoal filter with differential pressure gauge, G 3/8



Kategorija: [Activated carbon filter with differential pressure gauge](#)  
Šifra: **199819RIE**

(slika je simbolična)

### Kratek opis

Active charcoal filter with differential pressure gauge, 0.003 mg/m<sup>3</sup>, G 3/8, Input pressure 4 - 16 bar, Temp. 1.5 °C to 80 °C

For adsorbing vaporous media.

A micro-filter must be connected upstream if dried air is not available.

### Tehnične Specifikacije

|                                                      |                                                                      |
|------------------------------------------------------|----------------------------------------------------------------------|
| Element filtra                                       | non-woven medium, impregnated with activated carbon                  |
| Merjenje pretoka                                     | At P <sub>1</sub> = 7 bar and pressure drop Δ <sub>p</sub> = 0.1 bar |
| Navoj                                                | G 3/8                                                                |
| Ohišje                                               | Aluminium                                                            |
| Posoda filtra                                        | Aluminium                                                            |
| Rang filtra [μm]                                     | 0.00                                                                 |
| Vsebnost olja v ostanku [mg/m <sup>3</sup> ]         | 0.003                                                                |
| Min. sobna temperatura [°C]                          | 1.5                                                                  |
| Min. temperatura medija [°C]                         | 1.5                                                                  |
| Max. označeni razpon diferencialnega manometra [bar] | 2                                                                    |
| Max. vhodni tlak [bar]                               | 16                                                                   |
| C [mm]                                               | 23.5                                                                 |
| A [mm]                                               | 80.0                                                                 |
| Max. sobna temperatura [°C]                          | 80                                                                   |
| Max. temperatura medija [°C]                         | 80                                                                   |
| Učinkovitost [%]                                     | 99.9999                                                              |
| D [mm]                                               | 327.0                                                                |
| Pretok [l/min]                                       | 1000                                                                 |