

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Bimetalni termometer, zadaj, L1=100 mm / L2=80 mm, Ø 100

Kategorija: [Wika](#)
Šifra: **102800RIE**

Kratek opis

Bi-metallic thermometer, High quality design, Connection rear, for protective pipe L1=100 mm/L2=80 mm, Display range -30°C to 50°C
Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.
A thermowell (removable with locking screw) is required.

Tehnične Specifikacije

Prikaz območja min. [°C]	-30
Delovni tlak	Max. 25 bar (on thermowell)
Ohišje	CrNi steel
Okvir	CrNi steel
Položaj povezave	rear
Popravek prikaza	Trimming pointer
Povezava	Flush, with collar for thermowell, Ø 18 mm
Prednje steklo	Flat instrument glass
Primeren za termometer z dolžino	SR02 / SR12 / SR22
Stem	Ø 8 mm, CrNi steel
Stopnja rasti na območju skale - bar [bar]	0.5
Prikaz območja max. [°C]	50
Vrsta	52
Premer [mm]	100