

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Dušilna ploščica za NAMUR ventil, 5-potni, imbus vijak

Kategorija: [Flow regulators for NAMUR valves](#)
Šifra: **103665RIE**

Kratek opis

Throttle plate for NAMUR valves, Anodised aluminium, Temp. -20 °C to 70 °C, Working pressure 0.5 - 10 bar, 5-way, Knurled screw
Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard.
3/2-way flow regulators:
Independent regulation of the forward and return strokes of a single-acting pneumatic actuator.
5/2-way flow regulators:
Regulation of the forward and return strokes of a double-acting pneumatic actuator.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Delovanje	Knurled screw
Ohišje	Aluminium anodised
Srednje	Air, neutral gases (filtered)
Tesnilo	NBR
Min. delovni tlak [bar]	0.5
Obseg dobave	1 coding pin, 2 O-rings, 2 fixing screws
DN	5
Ffunkcija	5-way
Max. delovni tlak [bar]	10
Max. delovna temperatura [°C]	70
Pretok [l/min]	650