

End position feedback PA, inductive sensor, ATEX, 8,2V DC



Kategorija: [End position feedback, PA glass fiber reinforced, inductive NAMUR sensors](#)
Šifra: **117259RIE**

(slika je simbolična)

Kratek opis

End position feedback PA glass fiber reinforced, inductive sensor ATEX, NAMUR (NC), 8,2V DC, 1-3 mA, ambient temp. -25°C to 70°C
Robust and compact end position feedback with plastic housing.
- Actuator hole spacings 80x30mm or 130x30mm
- Height-adjustable assembly bridge for actuator shaft heights 20/30/40/50mm
- 3D position indicator also visible from a distance
- Easy-to-adjust, self-locking trip cam

Tehnične Specifikacije

Min. sobna temperatura [°C]	-25
IP zaščita	IP 67, acc. to DIN EN 60529
Kabelska uvodnica	M20x1.5
Nominalna preklopna zmogljivost	$\leq 1.0\text{mA}$ / $\geq 2.1\text{mA}$
Ohišje	PA
Opis	NJ2 -inductive sensor quadruple
Preklopna funkcija	Inductive (NAMUR NO/NC)
Različica	with inductive sensor ATEX type
Območje napetosti	8.2V DC
Max. sobna temperatura [°C]	70