

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## **Filter»FUTURA«PC zbir.5 µmVel.1,G 1/4Pol avt.**

Kategorija: [Filter with polycarbonate bowl and bowl guard](#)  
Šifra: **100145RIE**

### **Kratek opis**

Filter »FUTURA« with PC container and protective cage, 5 µm, Size 1, G 1/4, 1.5 - 16 bar, Temp. -10 °C to 50 °C, Semi-automatic  
Filters with excellent flow rates in modern design.

### **Tehnične Specifikacije**

|                                |                                                                    |
|--------------------------------|--------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                |
| Element filtra                 | Cellpor (PE)                                                       |
| Merjenje pretoka               | At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar |
| Navoj                          | G 1/4                                                              |
| Odtok kondenzata               | Semi-automatic                                                     |
| Ohišje                         | PA66 GF60                                                          |
| Posoda                         | Polycarbonate container with protective cage                       |
| Priključni navoj               | Material: Die-cast zinc                                            |
| Serijska                       | FUTURA                                                             |
| Srednje                        | Compressed air, neutral gases                                      |
| Tesnilo                        | NBR                                                                |
| Velikost                       | 1                                                                  |
| Min. vhodni tlak [bar]         | 1.5                                                                |
| Rang filtra [µm]               | 5                                                                  |
| Max. vhodni tlak [bar]         | 16                                                                 |
| C [mm]                         | 34.0                                                               |
| Max. temperaturno območje [°C] | 50                                                                 |
| A [mm]                         | 52.0                                                               |
| B [mm]                         | 164.0                                                              |
| Pretok [l/min]                 | 2200                                                               |