

Datum: 10.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Filter»G«,PC zbir.,Zaščitna kletka,5 µmVel. 300G 1/4

Kategorija: [Filter with polycarbonate bowl, bowl guard](#)  
Šifra: **116395RIE**

### Kratek opis

Filter »G« PC container, Protective cage, Mounting bracket,  
5 µm, Size 300, G 1/4, Input pres. max 10 bar, Working pres.  
1.5-9 bar  
Centrifugal separators with a sintered filter element.

### Tehnične Specifikacije

|                                 |                                                                            |
|---------------------------------|----------------------------------------------------------------------------|
| Merjenje pretoka                | At $P_1 = 8$ bar, $P_2 = 6$ bar<br>and pressure drop $\Delta p = 1$<br>bar |
| Navoj                           | G 1/4                                                                      |
| Odtok kondenzata                | Fully-automatic                                                            |
| Ohišje                          | Die-cast aluminium                                                         |
| Posoda                          | Polycarbonate container<br>with protective cage                            |
| Serija                          | G                                                                          |
| Tesnilo                         | NBR                                                                        |
| Min. delovni tlak [bar]         | 1.5                                                                        |
| Rang filtra [µm]                | 5                                                                          |
| Max. delovni tlak [bar]         | 9                                                                          |
| Max. vhodni tlak [bar]          | 10                                                                         |
| C [mm]                          | 21.0                                                                       |
| A [mm]                          | 51.0                                                                       |
| Max. sobna temperatura<br>[°C]  | 70                                                                         |
| Max. temperatura medija<br>[°C] | 70                                                                         |
| D [mm]                          | 143.0                                                                      |
| B [mm]                          | 164.0                                                                      |
| Velikost                        | 300                                                                        |
| Pretok [l/min]                  | 1550                                                                       |