



Filter reg.»FUTURA« PC, Vel. 4, G3/4, 0.5-16 bar, Avt.

Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)
Šifra: **151808RIE**

(slika je simbolična)

Kratek opis

Filter regulator »FUTURA« with PC container, Protective cage, Pressure gauge, 5 µm, Size 4, G 3/4, Control range 0.5-16 bar, Fully
Filter regulators with excellent flow rates in modern design.
The regulator knob can be latched and locked.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At P ₁ = 10 bar, P ₂ = 6.3 bar and pressure drop Δ _p = 1 bar
Navoj	G 3/4
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Poraba zraka	Yes
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Max. notranja poraba zraka	1.5 l/min (depending on secondary pressure)
Min. vhodni tlak [bar]	1.5
Velikost	4
Rang filtra [µm]	5
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	25
Max. temperaturno območje [°C]	50
A [mm]	85.0
C [mm]	137.0
B [mm]	343.0
Pretok [l/min]	13000