



Filter reg.»FUTURA«PCVel.1,G 3/8, 0.5-8 barAvt.

Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)
Šifra: **100125RIE**

(slika je simbolična)

Kratek opis

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 1, G 3/8, Control range 0.5-8 bar, Fully
Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Velikost	1
Min. vhodni tlak [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	8
Zaslon manometra max. [bar]	10
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
A [mm]	52.0
C [mm]	96.0
B [mm]	243.0
Pretok [l/min]	2500