



(slika je simbolična)

## Filter reg.»FUTURA«PCVel.4G 3/4, 0.5-8 barPol avto.

Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)

Šifra: **100122RIE**

### Kratek opis

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 4, G 3/4, Control range 0.5-8 bar, Semi  
Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

### Tehnične Specifikacije

|                                |                                                                         |
|--------------------------------|-------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                     |
| Element filtra                 | Cellpor (PE)                                                            |
| Membrane                       | NBR                                                                     |
| Merjenje pretoka               | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                          | G 3/4                                                                   |
| Odtok kondenzata               | Semi-automatic                                                          |
| Ohišje                         | PA66 GF60                                                               |
| Poraba zraka                   | Yes                                                                     |
| Posoda                         | Polycarbonate container with protective cage                            |
| Priključni navoj               | Material: Die-cast zinc                                                 |
| Serijska                       | FUTURA                                                                  |
| Srednje                        | Compressed air, neutral gases                                           |
| Tesnilo                        | NBR                                                                     |
| Min. krmilno območje [bar]     | 0.5                                                                     |
| Max. notranja poraba zraka     | 1.5 l/min (depending on secondary pressure)                             |
| Min. vhodni tlak [bar]         | 1.5                                                                     |
| Velikost                       | 4                                                                       |
| Rang filtra [µm]               | 5                                                                       |
| Max. krmilno območje [bar]     | 8                                                                       |
| Zaslon manometra max. [bar]    | 10                                                                      |
| Max. vhodni tlak [bar]         | 16                                                                      |
| Max. temperaturno območje [°C] | 50                                                                      |
| A [mm]                         | 85.0                                                                    |
| C [mm]                         | 137.0                                                                   |
| B [mm]                         | 326.0                                                                   |
| Pretok [l/min]                 | 13000                                                                   |