

Datum: 13.05.2024

(slika je simbolična)

Filter reg. »Stinard« Kov. pos.40 µmVel.2,G 3/8

Kategorija: [Filter regulator with metal bowl](#)Šifra: **100936RIE**

Kratek opis

Filter regulator »Standard«, Metal container and pressure gauge, 40 µm, Size 2, G 3/8, Input pressure max. 25 bar, 0.5 - 16 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Manuel
Ohišje	Die-cast zinc, painted silver
Posoda	Metal container
Serija	Standard
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Velikost	2
DN	11
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	25
Zaslon manometra max. [bar]	25
Rang filtra [µm]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	70.0
F [mm]	76.5
C [mm]	120.5
D [mm]	161.0
Pretok [l/min]	1500