

Datum: 13.05.2024



(slika je simbolična)

Filter reg. »Stinard«Kov. pos.5 µmVel.1,G 1/4

Kategorija: [Filter regulator with metal bowl](#)Šifra: **100934RIE**

Kratek opis

Filter regulator »Standard«, Metal container and pressure gauge, 5 µm, Size 1, G 1/4, Input pressure max. 25 bar, 0.5 - 16 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Manuel
Ohišje	Die-cast zinc, painted silver
Posoda	Metal container
Serijska	Standard
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Velikost	1
Rang filtra [µm]	5
DN	8
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	25
Zaslona manometra max. [bar]	25
A [mm]	54.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
F [mm]	62.0
C [mm]	106.5
D [mm]	133.5
Pretok [l/min]	900