



(slika je simbolična)

## Filter regulator »multifix-mali«, Kovinska posoda, G 1/4, 0.5-10

Kategorija: [Filter regulator with metal bowl, pressure gauge](#)  
Šifra: **100356RIE**

### Kratek opis

Filter regulator »multifix-mini«, Metal container, press. gauge, 5  $\mu\text{m}$ , G 1/4, Input pressure max. 16 bar, Control range 0.5-10 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

### Tehnične Specifikacije

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| Merjenje pretoka              | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop |
| Navoj                         | $\Delta_p = 1$ bar                                   |
| Odtok kondenzata              | G 1/4                                                |
| Ohišje                        | Semi-automatic                                       |
| Posoda                        | Die-cast zinc                                        |
| Serijska                      | Metal container                                      |
| Tesnilo                       | multifix-mini                                        |
| Vzmet pokrova motorja         | NBR                                                  |
| Min. krmilno območje [bar]    | POM-brass                                            |
| DN                            | 0.5                                                  |
| Rang filtra [ $\mu\text{m}$ ] | 5                                                    |
| Max. krmilno območje [bar]    | 10                                                   |
| Max. vhodni tlak [bar]        | 16                                                   |
| Zaslon manometra max. [bar]   | 16                                                   |
| A [mm]                        | 40.0                                                 |
| Max. sobna temperatura [°C]   | 60                                                   |
| Max. temperatura medija [°C]  | 60                                                   |
| C [mm]                        | 63.0                                                 |
| D [mm]                        | 99.0                                                 |
| B [mm]                        | 162.0                                                |
| Pretok [l/min]                | 1450                                                 |