



(slika je simbolična)

Filter regulator »multifix-mali«, PC zbiralnik, G 1/4, 0.5-10 bar

Kategorija: [Filter regulator with PC bowl and pressure gauge](#)
Šifra: **100354RIE**

Kratek opis

Filter regulator »multifix-mini«, PC container and press. gauge, 5 μm , G 1/4, Input pressure max. 16 bar, Control range 0.5-10 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10 \text{ bar}$, $P_2 = 6.3 \text{ bar}$ and pressure drop $\Delta p = 1 \text{ bar}$
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Serijska	multifix-mini
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
DN	5
Rang filtra [μm]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
A [mm]	40.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	63.0
D [mm]	102.5
B [mm]	165.5
Pretok [l/min]	1450