

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Filter »variobloc« s kovinsko posodo, Velikost 2, G 1/2

Kategorija: [Filter with metal bowl incl. sight glass](#)
Šifra: **125317RIE**

Kratek opis

Filter »variobloc« with metal container incl. viewing tube, Size 2, G 1/2, Input pressure max. 20 bar, Manual bleeder valve

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Metal container with viewing tube
Serija	variobloc
Tesnilo	NBR
Velikost	2
Max. vhodni tlak [bar]	20
C [mm]	26.0
Rang filtra [μm]	40
A [mm]	70.0
Max. sobna temperatura [$^{\circ}\text{C}$]	80
Max. temperatura medija [$^{\circ}\text{C}$]	80
B [mm]	202.0
Pretok [l/min]	3200