

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Filter z aktivnim ogljem brez diferencialnega manometra, G 3/8

Kategorija: [Activated carbon filter without diff. press. gauge](#)
Šifra: **101585RIE**

Kratek opis

Active charcoal filter without differential pressure gauge, 0.005 mg/m³, G 3/8, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C
For adsorbing vaporous media.
A micro-filter must be connected upstream if dried air is not available.

Tehnične Specifikacije

Element filtra	Activated carbon
Merjenje pretoka	At P ₁ = 6 bar and pressure drop Δ _p = 0.5%
Navoj	G 3/8
Ohišje	Aluminium
Posoda filtra	Aluminium
Vsebnost olja v ostanku [mg/m ³]	0.005
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	16
C [mm]	57.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	83.0
B2 [mm]	245.0
D [mm]	263.0
Pretok [l/min]	500