



(slika je simbolična)

Filter z aktivnim ogljem »FUTURA-mali« PC zbir. Vel. 0, G1/4

Kategorija: [Activated carbon filter with polycarbonate bowl](#)Šifra: **142453RIE**

Kratek opis

Active charcoal filter »FUTURA-mini« with PC container, 0.005 mg/m³, Size 0, G 1/4, Input pressure 0 - 12 bar, Temp. -10°C to 50°C

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.

Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon
Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 0.2 bar
Navoj	G 1/4
Ohišje	PA66 GF60
Posoda	Polycarbonate container
Priključni navoj	Plastic
Serijska	FUTURA-mini
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vsebnost olja v ostanku [mg/m ³]	0.005
Max. vhodni tlak [bar]	12
C [mm]	27.0
A [mm]	43.0
Max. temperaturno območje [°C]	50
B [mm]	125.0
Pretok [l/min]	470