

Datum: 11.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Filter z aktivnim ogljem»FUTURA« z PC zbir.Vel.1,G 3/8

Kategorija: [Activated carbon filter, PC bowl, bowl guard](#)
Šifra: **100192RIE**

Kratek opis

Active charcoal filter »FUTURA« with PC container and protective cage, 0.005 mg/m³, Size 1, G 3/8, Input pressure 0 - 16 bar
Activated carbon filters in modern design for compliance with strict compressed air purity requirements.
Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P ₂ = 6 bar and pressure drop Δ _p = 0.2 bar
Merjenje pretoka	G 3/8
Navoj	PA66 GF60
Ohišje	Polycarbonate container with protective cage
Posoda	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	1
Max. vhodni tlak [bar]	16
C [mm]	34.0
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	157.0
Pretok [l/min]	470