

Datum: 10.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Filter z aktivnim ogljem »variobloc«PC zbir.Vel. 2G 3/4

Kategorija: [Activated carbon filter with polycarbonate bowl](#)
Šifra: **100695RIE**

Kratek opis

Active charcoal filter »variobloc« with PC container, 0.003 mg/m³, Size 2, G 3/4, Input pressure max. 16 bar, Temp. max. 50 °C
Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

Tehnične Specifikacije

Kakovost zraka po ISO 8573.1	Class 1 dirt, class 1 oil
Merjenje pretoka	At P ₁ = 7 bar and pressure drop Δp = 0,2 bar
Navoj	G 3/4
Posoda	Polycarbonate container
Serija	variobloc
Vsebnost olja v ostanku [mg/m ³]	0.003
Velikost	2
Max. vhodni tlak [bar]	16
C [mm]	26.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	70.0
B [mm]	193.0
Pretok [l/min]	1300