

Datum: 10.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Filter z aktivnim ogljem »variobloc« Zašč. kletkaVel.1,G 3/8

Kategorija: [Activated carbon filter with PC bowl, bowl guard](#)
Šifra: **125326RIE**

Kratek opis

Active charcoal filter »variobloc« with PC container and protective cage, 0.003 mg/m³, Size 1, G 3/8, Input pressure max. 16 bar
Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

Tehnične Specifikacije

Kakovost zraka po ISO 8573.1	Class 1 dirt, class 1 oil
Merjenje pretoka	At P ₁ = 7 bar and pressure drop Δp = 0,2 bar
Navoj	G 3/8
Posoda	Polycarbonate container with protective cage variobloc
Serija	
Vsebnost olja v ostanku [mg/m ³]	0.003
Velikost	1
Max. vhodni tlak [bar]	16
C [mm]	22.0
A [mm]	48.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
B [mm]	142.0
Pretok [l/min]	1000