



(slika je simbolična)

Filter z regulatorjem tlaka, DVGW test, R 1 1/4

Kategorija: [Back-flushing filters with pressure regulator](#)
Šifra: **101425RIE**

Kratek opis

Back flush filter with pressure regulator, for potable water, DVGW tested, incl. pressure gauge, 90 µm to 110 µm, R 1 1/4

Combined station for filtering and regulating the pressure of drinking and domestic water in addition to well, process and cooling water for once-through cooling systems, consisting of a diaphragm pressure regulator with a pressure-reduced single-seated valve and a back-flushing filter.

The filter candle must be cleaned manually at regular intervals by back-flushing (flushing out dirt particles). Integrated back-flushing element with suction elements, back-flushing lever, wing lever for back-flushing element, hose connection for flushing water.

Tehnične Specifikacije

Cedilna košarica	Impact-resistant plastic
Merjenje pretoka	At pressure drop Δ_p =
Navoj	0.2 bar
Ohišje	R 1 1/4
Min. krmilno območje [bar]	Brass
Pretok KVS vrednost [m³/h]	2
Min. sobna temperatura [°C]	4
Min. temperatura vode [°C]	5
Max. krmilno območje [bar]	5
Max. vhodni tlak [bar]	6
Max. temperatura vode [°C]	16
DN	30
Max. sobna temperatura [°C]	32
A [mm]	40
Spodnja širina mrežice [µm]	79.7
B [mm]	110
C [mm]	213.0
	392.8