



## Glicerinski manometer, CrNi jeklo, G 1/2, -1 / +3 bar, Ø 100

Kategorija: [Wika](#)  
Šifra: **102390RIE**

(slika je simbolična)

### Kratek opis

Glycerine pressure gauge, CrNi steel safety design, Connection radial bottom, G 1/2, Measurement range -1 / +3 bar, Ø 100  
Glycerine-filled bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing). Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

### Tehnične Specifikacije

|                                            |                          |
|--------------------------------------------|--------------------------|
| Min. sobna temperatura [°C]                | -20                      |
| Min. temperatura medija [°C]               | -20                      |
| Merilno območje min. bar                   | -1                       |
| Material                                   | CrNi steel               |
| Material Prozessanschluss                  | CrNi steel               |
| Položaj povezave                           | radial on bottom         |
| Povezava                                   | G 1/2                    |
| Prednje steklo                             | Laminated safety glass   |
| Spodnja/Zgornja meja območja               | Vacuum/Positive pressure |
| Stopnja rasti na območju skale - bar [bar] | 0.1                      |
| Razred točnosti                            | 1.0                      |
| Merilno območje max. bar                   | 3                        |
| Max. sobna temperatura [°C]                | 60                       |
| Max. temperatura medija [°C]               | 100                      |
| Premjer [mm]                               | 100                      |
| Vrsta                                      | 233.30                   |