



(slika je simbolična)

Hidravlična spojka zakl. na obeh str.POMG 3/4 N.N.I.D. 13

Kategorija: [Hydraulic couplings, POM, female](#)
Šifra: **107717RIE**

Kratek opis

Hydraulic coupling locking on both sides, POM, G 3/4 IT, I.D. 13, Operating pressure max. 10 bar, Temp. -20 °C to 90 °C
Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.
Areas of application: manufacturing industry, chemical / pharmaceutical industry, food technology.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	Referred to medium temp. of 50 °C, static working pressure
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	POM (Delrin), white
Povezava	G 3/4 IT
Pritrdilni obroč	Stainless steel
Rokav	POM (Delrin), white
Tesnilo	NBR
Ventil	Stainless steel 1.4305
Vzmet	Stainless steel
Max. obratovalni tlak [bar]	10
DN	13
a/f [mm]	34
Max. sobna temperatura [°C]	90
Max. temperatura medija [°C]	90
Dolžina [mm]	96.0
Volumski pretok (zrak) [l/min]	4500