

Datum: 11.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Hitre spojke I.D. 19, zunanji navoj medenina, G 1 notranji navoj

Kategorija: [Quick disconnect coupling DN 19, female](#)
Šifra: **141565RIE**

Kratek opis

Quick-connect coupling I.D. 19, Bright brass, G 1 IT,
Operating pressure 0 - 35 bar, Med. / ambient temp. -20 °C
to 100 °C

"
Single-sided blocking and quick connect coupling with
extremely high flow performance.

To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

These quick disconnect couplings are not suitable for direct
attachment to pulsating tools.

We recommend using our vibration dampers, according to
ISO 6150 § 7.1.

Areas of application: Machine and plant engineering,
manufacturing industry, workshops.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 - 35 bar at 6 bar and $\Delta p = 0.5$ bar
Merjenje pretoka	Brass with a bare metal surface
Navojni kos	Brass with a bare metal surface
Ohišje	G 1 IT
Povezava	Brass with a bare metal surface
Rokav	NBR
Tesnilo	Brass with a bare metal surface
Ventil	Stainless steel
Vzmet	19
DN	41
a/f [mm]	100.0
Dolžina [mm]	100
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	8700 l/min (air)