

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Hitre spojke I.D. 19Z.N. Med.G 1 1/4 N.N.

Kategorija: [Quick disconnect coupling DN 19, female](#)
Šifra: **141566RIE**

Kratek opis

Quick-connect coupling I.D. 19, Bright brass, G 1 1/4 IT,
Operating pressure 0 - 35 bar, Med. / ambient temp. -20 °C
to 100 °C

"

Single-sided blocking and quick connect coupling with
extremely high flow performance.

To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

These quick disconnect couplings are not suitable for direct
attachment to pulsating tools.

We recommend using our vibration dampers, according to
ISO 6150 § 7.1.

Areas of application: Machine and plant engineering,
manufacturing industry, workshops.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 - 35 bar
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Navojni kos	Brass with a bare metal surface
Ohišje	Brass with a bare metal surface
Povezava	G 1 1/4 IT
Rokav	Brass with a bare metal surface
Tesnilo	NBR
Ventil	Brass with a bare metal surface
Vzmet	Stainless steel
DN	19
a/f [mm]	50
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Dolžina [mm]	102.0
Pretok	8700 l/min (air)