

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Hitre spojke I.D. 7.8, „Fi cevi I.D. 9

Kategorija: [Quick disconnect coupling DN 7.8, with hose stem](#)  
Šifra: **141520RIE**

### Kratek opis

Quick-connect coupling I.D. 7.8, Steel, Sleeve I.D. 9,  
Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

Single-sided blocking, high quality and robust quick connect coupling for high flow values.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, mining.

### Tehnične Specifikacije

|                              |                                   |
|------------------------------|-----------------------------------|
| Min. sobna temperatura [°C]  | -20                               |
| Min. temperatura medija [°C] | -20                               |
| Delovni tlak                 | 0 - 35 bar                        |
| Krogla                       | Stainless steel                   |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar |
| Navojni kos                  | Galvanised steel                  |
| Ohišje                       | Galvanised steel                  |
| Povezava                     | I.D. 9                            |
| Rokav                        | Galvanised steel                  |
| Tesnilo                      | NBR                               |
| Ventil                       | Die-cast zinc (zamac)             |
| Vzmet                        | Stainless steel                   |
| DN                           | 7.8                               |
| a/f [mm]                     | 19                                |
| Dolžina [mm]                 | 70.0                              |
| Max. sobna temperatura [°C]  | 100                               |
| Max. temperatura medija [°C] | 100                               |
| Pretok                       | 2000 l/min (air)                  |