



(slika je simbolična)

Kaljena spojka DN6, zunanji navoj, Medenina, M14x1.5 45°

Kategorija: [Temp. control coupl. DN 6, without shut-off valve](#)
Šifra: **107925RIE**

Kratek opis

Tempered coupling DN 6, Exterior thread, Brass 2.0401, M14x1.5 45°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C
Compatible with HASCO Z 8 system.
For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines.
Optionally with free passage, one or both sides sealing.
Female-threaded couplings and plugs with female-threaded PTFE seal.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Priključni navoj	M14x1.5 45°
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
Max. obratovalni tlak [bar]	15
a/f [mm]	17
Dolžina [mm]	47.0
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160