

Datum: 14.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Kamlok Hitro spajane spojka, C tip, 1.4401, cev I.D. 75

Kategorija: [Kamlok female coupler with hose stem, Part C](#)
Šifra: **108105RIE**

Kratek opis

Kamlok quick-connect socket, Hose supports, C type, Stainless steel 1.4401, Hose I.D. 75, for plug Ø 92 mm, Pressure max. 16 bar
High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection.
A male part and a female part are joined together by shifting the handles.
There is no need to turn the hose!
Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc.
All Kamlok quick coupling boxes and Kamlok closure boxes are supplied with NBR seal.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Tesnilo	NBR, resistant to oils and benzine
Max. obratovalni tlak [bar]	16
Za cev I.D.	75
Za vtič Ø [mm]	92
Max. temperaturno območje [°C]	95
A [mm]	131.8
C [mm]	151.5