

Datum: 14.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## komp. cilinder LINERdelujoč v dveh smerehbat Ø 25hod 20M5

Kategorija: [Metalwork](#)  
Šifra: **106057RIE**

### Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 25, Stroke 20, M5, Working pressure max. 10 bar, Temp. -10°C to 60 °C  
New series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                        |
|--------------------------------|----------------------------------------|
| Min. temperaturno območje [°C] | -10                                    |
| Bat                            | POM                                    |
| Batnica                        | C45 steel, hard chrome-plated          |
| ET batnice                     | M8                                     |
| Ffunkcija                      | double-acting                          |
| Gewinde Kolbenstange           | male piston rod                        |
| Magnet                         | with magnet                            |
| Ovoj                           | Anodised aluminium jacket with T-slots |
| Povezava                       | M5                                     |
| Serijska                       | LINER series                           |
| Standard                       | acc. to ISO 21287                      |
| Tesnilo                        | NBR                                    |
| Min. nastavljeni tlak [bar]    | 0.6                                    |
| Max. delovni tlak [bar]        | 10                                     |
| Stroke [mm]                    | 20                                     |
| Bat Ø [mm]                     | 25                                     |
| Max. temperaturno območje [°C] | 60                                     |