

Datum: 10.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Kont. ventil, z navojem (vhodni) - (izhodni), G 1/4, 8

Kategorija: [Metalwork](#)
Šifra: **106810RIE**

Kratek opis

Check valve »lineonline«, Thread (inlet) - hose (outlet), G 1/4, for hose Ø 8 mm, Operating pressure 0.5 to 12 bar
These valves ensure that compressed air only flows in one (i.e. the desired) direction. The valve closes when inlet pressure is lost and maintains the working pressure that is present downstream.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	G 1/4
Notranji deli	Nickel-plated brass, brass, technopolymer, stainless steel
Pnevmatski simboli	On housing
Telo	Technopolymer
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.5
Za cevi Ø [mm]	8
Max. obratovalni tlak [bar]	12
l [mm]	18.7
B [mm]	26.0
Max. temperaturno območje [°C]	60
A [mm]	70.8
Pretok pri 6,3 bar in Δp 1,0 bar [l/min]	480