



krogelni ventil fina nastavitvev, nikljana lahka medenina, Rp 3/4

Kategorija: [Potable water ball valves with fine adjustment](#)
Šifra: **138874RIE**

(slika je simbolična)

Kratek opis

Ball valve fine adjustment, Potable water suitable, nickel-plated bright brass, Temp. -15°C to 120°C, Rp 3/4, DN 20, PN max 50 bar

Brass ball valves in the standard series with fine adjustment.

Unlike our classic standard ball valves (open-close function), this model features a special stem technology that allows finely modulated opening and closing of the line.

The flow rate can be regulated extremely precisely as a result.

The cock is made of low-lead brass with a bare brass surface on the inside. It is thus safe to use with drinking water. This valve complies with the European standard EN 13828 and the working paper DVGW W 570.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
DVGW odobritev	DIN EN 13828:2003-12, DVGW W 570
Kolo	Plastic
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	Rp 3/4
Ohišje	Nickel-plated brass (outside), brass with a bare metal surface (inside)
Standardni navoj	Thread acc. to ISO 7/1
Stebelno tesnilo	PTFE / NBR
DN	20
PN [bar]	50
L [mm]	69.6
B [mm]	75.6
A [mm]	83.2
Max. delovna temperatura [°C]	120