



(slika je simbolična)

## krogelni ventil medenina, električni vklop, 230 V AC, 50 Hz, Rp 2

Kategorija: [Brass ball valve, electric actuator 230 VAC, 50 Hz](#)  
Šifra: **103699RIE**

### Kratek opis

Brass ball valve, Electr. actuation drive, 230 V AC, 50 Hz,  
Operating temperature -20 °C to 70 °C, Rp 2, DN 50, PN  
max. 25 bar  
Voltage range 230 VAC, 50 Hz or 24 VDC.  
2-way cock, full bore, for neutral gases and liquids.  
Reversible electric rotary actuator.

### Tehnične Specifikacije

|                               |                              |
|-------------------------------|------------------------------|
| Min. sobna temperatura [°C]   | -30                          |
| Min. delovna temperatura [°C] | -20                          |
| Gred izbirnika                | Hard chrome-plated brass     |
| Indikator položaja            | Manually operated            |
| IP zaščita                    | IP 68                        |
| Krogelno tesnilo              | PTFE, glass fibre-reinforced |
| Krogla                        | Hard chrome-plated brass     |
| Material                      | Nickel-plated brass          |
| Montažna prirobnica           | ISO 5211                     |
| Navoj                         | Rp 2                         |
| Ohišje                        | Aluminium powder-coated      |
| Tesnilo gredi izbirnika       | FKM                          |
| Čas aktivacije [sec.]         | 15                           |
| PN [bar]                      | 25                           |
| Delovni cikel [%]             | 30                           |
| Relativna vlažnost            | 30 % to 95 %                 |
| D [mm]                        | 44.0                         |
| DN                            | 50                           |
| a/f [mm]                      | 70                           |
| Max. delovna temperatura [°C] | 70                           |
| Max. sobna temperatura [°C]   | 70                           |
| L [mm]                        | 140.0                        |
| A [mm]                        | 153.0                        |
| B [mm]                        | 199.5                        |
| Napetost                      | 230 VAC, 50 Hz               |