



krogelni ventil medenina, pnevmatski vklop duble-acting, Rp 2

Kategorija: [Brass ball valve, double-acting actuator](#)
Šifra: **158802RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, NAMUR, double-acting, Operating temp. -20 °C to 150 °C, Rp 2, DN 50, PN max. 16 bar
Ball valves with pneumatic actuator.
Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura aktuatorja [°C]	-20
Min. delovni tlak krogelnega ventila [°C]	-20
Adapter ventila	Integrated to NAMUR
Material krogelnega ventila	Nickel-plated brass, with flange plate ISO 5211
Navoj	Rp 2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.6
Max. vodeni tlak aktuatorja [bar]	8.4
Max. delovni tlak krogelnega ventila [bar]	16
DN	50
Max. delovna temperatura aktuatorja [°C]	80
Kot vrtenja [°]	90
L [mm]	134.0
B [mm]	143.8
Max. delovni tlak krogelnega ventila [°C]	150
A [mm]	174.2