

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



krogelni ventil medenina, pnevmatski vklop enojno delovanje, Rp 2

Kategorija: [Brass ball valve, single-acting actuator](#)
Šifra: **103577RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, single-acting,
Operating temperature -20 °C to 150 °C, Rp 2, DN 50, PN
max. 16 bar
Ball valves with pneumatic actuator.
Pneumatic, double-piston, part-turn actuator, double-rocker
principle.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Max. vodeni tlak [bar]	5.6
Max. obratovalni tlak [bar]	16
DN	50
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
L [mm]	134.0
Max. delovna temperatura [°C]	150
B [mm]	155.0
A [mm]	240.0