



(slika je simbolična)

## krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 2

Kategorija: [Stainless steel ball valve, double-acting actuator](#)  
Šifra: **103587RIE**

### Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 2, PN max. 40 bar  
Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

### Tehnične Specifikacije

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Min. delovna temperatura [°C]  | -20                                          |
| Min. temperaturno območje [°C] | -20                                          |
| Adapter ventila                | Supplied as standard                         |
| Material                       | Stainless steel                              |
| kroglne ventila                | 1.4401/1.4301/1.4310/1.4408, with ISO flange |
| Navoj                          | Rp 2                                         |
| Pogonski material              | Anodised aluminium                           |
| Premaz za kroglne ventil       | PTFE / FKM                                   |
| Premaz za pogon                | NBR                                          |
| Različica                      | double-acting                                |
| Max. vodeni tlak [bar]         | 5.6                                          |
| PN [bar]                       | 40                                           |
| DN                             | 50                                           |
| Max. temperaturno območje [°C] | 80                                           |
| Kot vrtenja [°]                | 90                                           |
| L [mm]                         | 125.0                                        |
| Max. delovna temperatura [°C]  | 150                                          |
| A [mm]                         | 169.0                                        |
| B [mm]                         | 196.0                                        |