



(slika je simbolična)

krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 3/4

Kategorija: [Stainless steel ball valve, single-acting actuator](#)
Šifra: **103590RIE**

Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, single-acting, Operating temp. -20 °C to 150 °C, Rp 3/4, PN max. 100 bar

Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange
Navoj	Rp 3/4
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Max. vodeni tlak [bar]	5.6
DN	20
L [mm]	70.0
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
PN [bar]	100
Max. delovna temperatura [°C]	150
B [mm]	163.0
A [mm]	240.0