

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## krogelni ventil nerjavno jeklo, za DIN 3202-M3, G 1 1/2

Kategorija: [Ball valves 3-piece, length acc. to DIN 3202-M3](#)  
Šifra: **135916RIE**

### Kratek opis

Stainless steel ball valve, 3-piece, length acc. to DIN 3202-M3, G 1 1/2, DN 40, Operating temp. -20 °C to 180 °C, PN max. 63 bar

### Tehnične Specifikacije

|                                |                                                          |
|--------------------------------|----------------------------------------------------------|
| Min. delovna temperatura [°C]  | -20                                                      |
| Bore diameter padlock ISO 5211 | ca. 7.7 mm<br>F 05 / F 07                                |
| Krogelno tesnilo               | PTFE (15 % glass fibre reinforced)                       |
| Krogla                         | Stainless steel 1.4401                                   |
| Navoj                          | G 1 1/2                                                  |
| Ohišje                         | Stainless steel 1.4408                                   |
| Ročica                         | Stainless steel 1.4301, with plastic coating             |
| Standardni navoj               | G thread acc. to DIN EN ISO 228-1, flange plate ISO 5211 |
| Stebelno tesnilo               | PTFE                                                     |
| C Ø [mm]                       | 38.0                                                     |
| DN                             | 40                                                       |
| PN [bar]                       | 63                                                       |
| B [mm]                         | 113.5                                                    |
| L [mm]                         | 120.0                                                    |
| Max. delovna temperatura [°C]  | 180                                                      |
| A [mm]                         | 190.0                                                    |