

Datum: 11.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## krogelni ventil, visoki tlak, G notranji navoj, jeklo, G 1/2

Kategorija: [High-pressure ball valve, steel, G female thread](#)  
Šifra: **103517RIE**

### Kratek opis

Ball valve, High pressure design, G interior thread, Steel, Operating temperature -10 °C to 100 °C, G 1/2, DN 12, PN max. 500 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.

- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.

- With female pipe thread acc. to DIN ISO 228-1 (BSP).

### Tehnične Specifikacije

|                               |                          |
|-------------------------------|--------------------------|
| Min. delovna temperatura [°C] | -10                      |
| Bore inball                   | Full bore                |
| Gred izbirnika                | Steel                    |
| Kontrolno kroglično tesnilo   | POM                      |
| Krogla                        | Hard-chrome plated steel |
| Navoj                         | G 1/2                    |
| Ohišje                        | Steel                    |
| Tesnilo gredi izbirnika       | NBR                      |
| DN                            | 12                       |
| L [mm]                        | 82.0                     |
| B [mm]                        | 92.0                     |
| Max. delovna temperatura [°C] | 100                      |
| A [mm]                        | 112.0                    |
| Max. obratovalni tlak [bar]   | 500                      |